

REPORT DOCUMENTATION PAGE			Form Approved OMB NO. 0704-0188	
<small>Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comment regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204 Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.</small>				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE 8 May 96		3. REPORT TYPE AND DATES COVERED Final - 16 Dec 91 - 15 Dec 95
4. TITLE AND SUBTITLE Transitions and Defects in Crystals			5. FUNDING NUMBERS	
6. AUTHOR(S) Mitchell Luskin, Richard James			DAAL03-92-G-0003	
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Grants and Contracts Office of Research and Technology Transfer Administration University of Minnesota Suite 201, 1100 Washington Avenue South Minneapolis, MN 55415-1226			8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army Research Office P.O. Box 12211 Research Triangle Park, NC 27709-2211			10. SPONSORING / MONITORING AGENCY REPORT NUMBER ARO 28987.10-MA	
11. SUPPLEMENTARY NOTES The views, opinions and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy or decision, unless so designated by other documentation.				
12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited.				
13. ABSTRACT (Maximum 200 words) The primary objective of this research has been to give strategies for improving shape memory and magnetostrictive materials based on reliable mathematical and computational models. Our theoretical research has led to the prediction of a new type of material, that combines the shape memory and magnetostrictive effects. Also, relying on experimental data obtained in our laboratory, we have been led to model the kinetics and hysteresis in a Cu-Al-Ni shape memory alloy by a new "wiggly energy" concept: many little wiggles are superimposed on the energy to reflect small scale microstructural changes. We have developed has rigorous theory for the analysis of the approximation of microstructure which will allow the development of efficient and reliable numerical methods for microstructure. Our research group has also developed methods and codes which have been used to compute complex equilibrium and dynamical microstructures.				
14. SUBJECT TERMS shape memory materials, magnetostrictive materials, microstructure, thin films, numerical methods			15. NUMBER OF PAGES 9	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OR REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED	20. LIMITATION OF ABSTRACT UL	

FINAL TECHNICAL REPORT - DAAL03-92-G-0003

Transitions and Defects in Crystals

December 16, 1991 – December 15, 1995

Mitchell Luskin and Richard James

University of Minnesota

May 6, 1996

STATEMENT OF PROBLEM STUDIED

In general, the central problem to be overcome is to find better materials. For a wide spectrum of technologies the main bottleneck is that current materials fall short of desired performance goals. While design, control and processing are all important in reaching these goals, the main issue is the materials themselves. The specific goal of this research is to give strategies for improving shape memory and magnetostrictive materials based on reliable mathematical models, studied via modern computational methods. The improvements are aimed at actuator applications.

The main opportunity to be seized at this time in the study of materials is the behavior and synthesis of materials at small scales. The emerging near-term route is thin films. It is becoming possible to synthesize many small scale devices on a wafer using integrated circuit technology. The field is now entirely driven by experiment; new methods are tried that are experimental extensions of what worked previously. Mathematical modeling and computation have an important role to play in this area, by predicting beforehand what properties are expected and by providing optimal designs. There is real chance for new discoveries here, as thin films behave entirely differently from bulk materials.

Our theoretical research has led to the prediction of a new type of material, that combines the shape memory and magnetostrictive effects. We have termed such a material a "magneto-memory" material. We have given a strategy for finding such a material, based on 1) arranging a martensitic transformation to be near a ferromagnetic transition, and 2) adjusting the lattice parameters of the material to satisfy "special relations" that promote desirable domain structures for microstructural rearrangements. This new material is predicted to have magneto-elastic strains that are more than

an order of magnitude larger than current giant magnetostrictive materials. This strategy is now being implemented by Wuttig and James.

There are two main puzzles in the mathematical modeling of active materials, that directly affect actuator applications. They are the related topics of hysteresis and kinetics. A new model of the kinetics of transformation between two variants of martensite has been given, based on a "wiggly energy" concept (see below). This shows good agreement with experiment, for a wide variety of different experiments: inner and outer hysteresis loops, creep tests, and various far from equilibrium tests. More importantly, it gives an understanding of the origins of hysteresis in terms of microstructure.

The main potential payoff is new materials for ARO applications. We aim for very specific strategies to be used for the improvement of materials, and explicit mathematical models. We do not do phenomenological modeling; the models we develop are based on fundamental transformation properties, such as lattice parameters, crystallographic symmetries, latent heat, saturation magnetization, etc. The reason for this approach is that the mathematical and computational models can then be used in the direct design of materials, by asking the question (as we do) of how do the predictions change when the fundamental properties change. More importantly, we look for special properties that give unusual or optimal behavior.

Since this research gives such explicit predictions, it entails a certain amount of risk. The predictions are periodically checked by direct comparison with experiment (currently by Tickle, Wuttig, De Graef).

SUMMARY OF MOST IMPORTANT RESULTS

Our theoretical research has led to the prediction of a new type of material, that combines the shape memory and magnetostrictive effects. We have termed such a material a "magneto-memory" material. We have given a strategy for finding such a material, based on 1) arranging a martensitic transformation to be near a ferromagnetic transition, and 2) adjusting the lattice parameters of the material to satisfy "special relations" that promote desirable domain structures for microstructural rearrangements. This new material is predicted to have magneto-elastic strains that are more than an order of magnitude larger than current giant magnetostrictive materials. This strategy is now being implemented by Wuttig and James. The existence of

such a material became clear after studies of giant magnetostriction [18]

There are two main puzzles in the mathematical modeling of active materials, that directly affect actuator applications. They are the related topics of hysteresis and kinetics. Relying on the experiments of Chu [10], Abeyaratne, Chu and James [2, 1] have been led to model the kinetics and hysteresis in a Cu-Al-Ni shape memory alloy by a new "wiggly energy" concept: many little wiggles are superimposed on the energy to reflect small scale microstructural changes. In this alloy the wiggles are due to the presence of thousands of tiny needles in the specimen [20], and the passage out of a local minimum corresponds to a tip splitting event. The predictions show good agreement with experiment, for a wide variety of different experiments: inner and outer hysteresis loops, creep tests, and various far from equilibrium tests. More importantly, the model gives an understanding of the origins of hysteresis in terms of microstructure. The idea has been extended to the analysis of the friction between clean surfaces [24], giving a model that explicitly relates the surface roughness to static friction (The authors are currently trying to predict roughness profiles that minimize or maximize friction; they also have set up a simple experimental program to measure the surface roughness of various surfaces by the atomic force microscope and then to compare the predictions of theory with measurements of macroscopic static friction).

Together with G. Gioia [13] and K. Bhattacharya [9], James has recently been trying some thin film calculations. By scaling a film thinner and thinner, it is found there is a mismatch of terms of the energy: certain terms are much larger than others. This can be used as the basis of a rigorous asymptotic argument giving a general limiting thin film theory. We have tried out this kind of argument for micromagnetic and martensitic energies. The results look to be extremely useful for predicting the behavior of this films, and point to major advantages of epitaxy.

Luskin gave the first analysis of the approximation of martensitic microstructure for a physically realistic, multi-dimensional crystalline energy [30, 31]. He developed this analysis for the orthorhombic to monoclinic (double well) transformation [31] and then extended the analysis with his graduate student, Bo Li, to the cubic to tetragonal (triple well) transformation [29]. He applied the approximation theory developed in his analysis of microstructure to obtain error estimates for the numerical approximation of microstructure by the finite element method. This analysis gives a theoretical basis for the computational projects described in the proposal and should make possible the development of more effective and reliable algorithms.

Luskin and his post-doc, Peter Klouček, have developed methods and a code to investigate fully three-dimensional dynamical phenomena associated with the propagation of the interface separating the martensitic and the austenitic phase in some indium-thallium shape-memory alloys [27, 28]. This dynamical problem is extremely challenging since the multi-well structure of the energy density leads to an ill-posed problem (in the absence of surface stress and viscous stress) for the linearized momentum equation about some strains. They have been able to develop stable time-discretization methods and efficient techniques for the solution of the linear equations at each time step even though the energy density is non-convex.

The computational experiments of Luskin and Klouček have simulated the development of martensitic microstructure and the propagation of the austenitic-martensitic phase boundary which separates the homogeneous austenitic phase from the microstructured martensitic phase. They have also done computational studies of the effects of surface stress and viscous stress on the dynamics. In [26], Klouček, Li, and Luskin have given an analysis of a nonconforming finite element method which has been used successfully to compute the dynamics of the martensitic transformation [27].

Luskin and his graduate student Bo Li have developed a numerical model for the simulation of the biaxial experiments of Chu described in [10, 5, 11].

In some shape memory alloys certain atomic scale relaxation effects take place that significantly affect long term performance. It is particularly prevalent in the Cu-based materials, and in several cases makes unusable otherwise good shape memory alloys. A new nonlinear dynamic model of this relaxation was given [8]. It shows excellent agreement with experimental measurements of the slow evolution of hysteresis loops, and the long-time "creep" of transformation temperature.

New methods for analyzing microstructure have been given, following our earlier work [3, 7].

PUBLICATIONS

- [1] R. Abeyarantne, C. Chu, and R. James. Kinetics of materials with wiggly energies: theory and application to the evolution of twinning microstructures in Cu-Al-Ni shape memory alloy. *Phil. Mag. A*. in press.

- [2] R. Abeyaratne, C. Chu, and R. James. Kinetics and hysteresis in martensitic single crystals. In L.C. Brinson and B. Moran, editors, *Proc. Symposium on the Mechanics of Phase Transformations and Shape Memory Alloys*. ASME-AMD-189, 1994.
- [3] J. M. Ball and R. James. Proposed experimental tests of a theory of fine microstructure and the two-well problem. *Phil. Trans. Royal Soc. London*, A338:389–450, 1992.
- [4] J. M. Ball and R. James. Theory for the microstructure of martensite and applications. In C.M. Wayman and J. Perkins, editors, *Proc. of the International Conference on Martensitic Transformations*. Monterey Institute for Advanced Studies, 1993.
- [5] J.M. Ball, C. Chu, and R. James. Hysteresis in martensitic phase transformations. *J. de Physique IV*, 5:245–251, 1995. ICOMAT-95.
- [6] J.M. Ball and R. James. Local minimizers and phase transformations. In *Proc. ICIAM-95*, 1995.
- [7] K. Bhattacharya, N. Firoozye, R. James, and R. Kohn. Restrictions on microstructure. In *Proc. Royal Soc. Edinburgh*, volume 124A, pages 843–878, 1994.
- [8] K. Bhattacharya, R. James, and P. J. Swart. A nonlinear dynamic model for twin relaxation with applications to Au 47.5at.%Cd and other shape-memory materials. In M. Yoo and M. Wüthig, editors, *Twinning in Advanced Material*. Proc. TMS symposium, 1996.
- [9] K. Bhattacharya and R. D. James. Theory of martensitic transformations in thin films. manuscript, 1996.
- [10] C. Chu and R. James. Biaxial loading experiments on Cu-Al-Ni single crystals. In *Experiments in Smart Materials and Structures*, volume 181, 1993. ASME-AMD.
- [11] C. Chu and R. James. Analysis of microstructures in Cu-14.0% Al-3.9% Ni by energy minimization. *J. de Physique IV*, 5:143–149, 1995. ICOMAT-95.

- [12] Charles Collins, Mitchell Luskin, and James Riordan. Computational results for a two-dimensional model of crystalline microstructure. In J. Ericksen, R. James, D. Kinderlehrer, and M. Luskin, editors, *Microstructure and Phase Transitions*, pages 51–56, New York, 1993. Springer-Verlag. IMA Volumes in Mathematics and Its Applications, vol. 54.
- [13] G. Gioia and R. D. James. Micromagnetics of thin films. manuscript, 1996.
- [14] R. James. Deformation of shape-memory materials. In *Proc. of the Materials Research Society Symposium on Shape-Memory Materials*, 1992.
- [15] R. James. Hysteresis in phase transformations. In *Proc. ICIAM-95*, 1995.
- [16] R. James and D. Kinderlehrer. Laminate structures in martensite. In *Proc. Workshop on Composite Media and Homogenization*, Trieste. SISSA. to appear.
- [17] R. James and D. Kinderlehrer. Mathematical approaches to the study of smart materials. In H. T. Banks, editor, *Proc. SPIE Conference on Smart Materials*, volume 1919, 1993.
- [18] R. James and D. Kinderlehrer. A theory of magnetostriction with applications to $Tb_x Dy_{1-x} Fe_2$. *Phil. Mag. B*, 68:237–274, 1993.
- [19] R. James and D. Kinderlehrer. A theory of magnetostriction with applications to Terfenol-D. In *Journal of Applied Physics – Supplemental Issue of the Proceedings of the Sixth Joint MMM-Intermag Conference*, Albuquerque, NM, June 20-23, 1994.
- [20] R. James, R.V. Kohn, and T.W. Shield. Modeling the branched needle microstructures at the edge of a martensite laminate. *J. de Physique IV*, 5:253–259, 1995. ICOMAT-95.
- [21] R. James and X. Liu. Stability of fiber networks under biaxial stretching. *Journal of Applied Mechanics*, 62/7:398–406, 1995.
- [22] R. James and S. Müller. Internal variables and fine-scale oscillations in micromagnetics. *Continuum Mech. Thermodyn.*, 6:291–336, 1994.

- [23] R. James and S. Spector. Remarks on $W^{1,p}$ -quasiconvexity, interpenetration of matter and function spaces for elasticity. *Ann. Inst. H. Poincaré*, 9:1–18, 1992.
- [24] R. D. James and H. Tsai. A theory of friction that accounts for the asperities. manuscript, 1996.
- [25] R. James D. Kinderlehrer. Frustration and microstructure: an example in magnetostriction. In C. Bandle, J. Benelmans, M. Chipot, M. Grüter, and J. St. Jean Paulin, editors, *Progress in partial differential equations: calculus of variations, applications*, volume 267. Pitman Research Notes in Mathematics, Longmans, 1992.
- [26] Petr Klouček, Bo Li, and Mitchell Luskin. Analysis of a class of nonconforming finite elements for crystalline microstructures. *Math. Comput.*, 67, 1996.
- [27] Petr Klouček and Mitchell Luskin. The computation of the dynamics of martensitic microstructure. *Continuum Mech. Thermodyn.*, 6:209–240, 1994.
- [28] Petr Klouček and Mitchell Luskin. Computational modeling of the martensitic transformation with surface energy. *Mathematical and Computer Modelling*, 20:101–121, 1994.
- [29] Bo Li and Mitchell Luskin. Finite element analysis of microstructure for the cubic to tetragonal transformation. Technical Report 1373, IMA, 1996.
- [30] Mitchell Luskin. On the computation of crystalline microstructure. *Acta Numerica*, 1996.
- [31] Mitchell Luskin. Approximation of a laminated microstructure for a rotationally invariant, double well energy density. *Numer. Math.*, to appear in 1996. IMA Preprint # 1325, 1995.
- [32] Mitchell Luskin and Charles Collins. Computational results for martensitic twinning. In Perkins and Wayman, editors, *Proceedings of the International Conference on Martensitic Transformations*, pages 83–88, Carmel, California, 1993. Monterey Institute of Advanced Studies.

- [33] Mitchell Luskin and Ling Ma. Analysis of the finite element approximation of microstructure in micromagnetics. *SIAM J. Numer. Anal.*, 29:320–331, 1992.
- [34] Mitchell Luskin and Ling Ma. Numerical optimization of the micromagnetics energy. In *Mathematics in Smart Materials*, pages 19–29. SPIE, 1993.
- [35] Mitchell Luskin and T.-W. Pan. Nonplanar shear flows for nonaligning nematic liquid crystals. *Journal of Non-Newtonian Fluid Mechanics*, 42:369–384, 1992.

PARTICIPATING SCIENTIFIC PERSONNEL

Mitchell Luskin, Principal Investigator
 Richard James, Co-Principal Investigator
 Pierre Gremaud, Postdoctoral Fellow (currently Assistant Professor at North Carolina State University)
 Petr Klouček, Post-Doc (accepted Assistant Professor position at Rice University)
 Hungyu Tsai, Postdoctoral Fellow (currently Assistant Professor at Michigan State)
 Brian Berg, Graduate Student, Ph.D. 1993 (currently Principal Scientist, Flexmedics Corporation)
 Tim Brule, Graduate Student
 Chunhwa Chu, Graduate Student, Ph.D. 1993 (currently job hunting)
 Antonio De Simone, Graduate Student, Ph.D. 1992 (currently Ricercatore, Universite di Roma "Tor Vergata")
 Shad Jessoritz, Graduate Student, M.S. 1996 (currently in Air Force)
 Bo Li, Graduate Student, Ph.D. to be obtained May, 1996 (accepted Post-Doctoral position at UCLA)
 Narendra Simha, Graduate Student, Ph.D. 1994 (currently Postdoctoral Fellow at CalTech)
 Robert Tickle, Graduate Student